

## SPECIFICATION SHEET

JOB NAME: \_\_\_\_\_  
LOCATION: \_\_\_\_\_  
QUOTE/REF#: \_\_\_\_\_



The **ALP-140** is an Architectural Grade LED extrusion profile designed for linear LED strips up to 28mm wide. Made from high quality aluminum, these extrusions provide superior thermal management for higher wattage LED strips and prolong the overall lifetime of your lighting system. The **ALP-140** is manufactured with a patented frosted diffuser for maximum lumen output and wide beam distribution. The **ALP-140** also helps protect LED's from dust and other undesirable elements, which can shorten the lifetime of the LED.

### FEATURES

- Customizable
- Ideal for surface mount applications
- Durable, military grade aluminum
- Protects LED systems from dust and other elements
- Dissipates heat from LED, prolonging its lifetime

### SPECIFICATIONS

TYPE	Surface mount
AVAILABLE LENGTHS	49.25" and 98.5"
FINISH	Anodized Silver
LENS OPTIONS	Frosted

Compatible with LED strips up to 1.12" / 1 1/8" / 28mm wide.


LED tape light sold separately.

Remote mounted low voltage power supply sold separately.

Power supplies available in 120V and 277 options.

### COMPONENTS

PROFILE	ALP-140
LENS	ALP-140-LN
END CAP	ALP-140-EC
CABLE SUSPENSION KIT	ALP-CS12
POWER FEED KIT	ALP-CF
NON-POWER FEED KIT	ALP-CSB
Frosted lens included with each channel.	
Two (2) end caps included with every channel.	
Custom color finishes available (powder coating).	



### ORDERING GUIDE

ALP-140			
MODEL	SIZE	LENS	LIGHT ENGINE
	49 - 49.25 Inches 98 - 98.5 Inches	FR - Frosted Lens	See p.3 for compatible tape lights

SUSPENSION KIT ACCESSORIES (REQUIRED FOR SUSPENSION OPTION - SOLD SEPARATELY)

ALP-CS12 | Cable Suspension Kit



ALP-CF | Power Feed Kit

ALP-CF-WH | White Power Feed Kit

ALP-CF-BK | Black Power Feed Kit



ALP-CSB | 2" Non-Power Feed Kit

ALP-CSB-WH-2 | 2" White Feed Kit

ALP-CSB-BK-2 | 2" Black Feed Kit



ALP-CSB | 5" Non-Power Feed Kit

ALP-CSB-WH-5 | 5" White Feed Kit

ALP-CSB-BK-5 | 5" Black Feed Kit



## TAPE LIGHT - CHANNEL COMPATIBILITY

	INDOOR LED STRIPS		OUTDOOR LED STRIPS		RGB & RGBW
✓	LSM-15   1.5W / FT.   120 Lumens	✓	LSMW-15   1.5W / FT.   120 Lumens	✓	LSP-20RGB   2.2W / FT.   82 Lumens
✓	LSM-25   2.2W / FT.   185 Lumens	✓	LSMW-25   2.2W / FT.   185 Lumens	✓	LSP-50RGB   4.4W / FT.   165 Lumens
✓	LSM-30   3.0W / FT.   250 Lumens	✓	LSMW-30   3.0W / FT.   250 Lumens	✓	LSP-80RGB   8.8W / FT.   720 Lumens
✓	LSM-45   4.4W / FT.   370 Lumens	✓	LSMW-60   6.0W / FT.   500 Lumens	✓	LSP-50RGBW   4.4W / FT.   165 Lumens
✓	LSM-55   5.5W / FT.   500+ Lumens			✓	LSP-80RGBW   8.8W / FT.   720 Lumens
✓	LSP-50   4.4W / FT.   380 Lumens				
✓	LSM-60   6.0W / FT.   500 Lumens				
✓	LSM-60MX   6.0W / FT.   500 Lumens				
✓	LSP-80   8.8W / FT.   720 Lumens				
✓	LSM-70HF   6.6W / FT.   698 Lumens				
✓	LSM-90HF   7.9W / FT.   930 Lumens				