


SPECIFICATION SHEET



SPECIFICATIONS

| INPUT VOLTAGE | 12V DC Constant Voltage |
|-----------------------|-------------------------|
| POWER CONSUMPTION | 3.0W per puck |
| LUMEN OUTPUT | 240Lm |
| BEAM ANGLE | 120° |
| ССТ | 3000K |
| CRI | 90+ |
| DIMMING | MLV, ELV and TRIAC |
| MOUNTING | Surface mount |
| OPERATING TEMPERATURE | -4 ~ 122°F (-20 ~ 50°C) |
| AMBIENT TEMPERATURE | -4 ~ 176°F (-20 ~ 80°C) |
| LUMEN MAINTENANCE | 50,000 hrs. |
| FINISH OPTIONS | Black and Silver |
| WARRANTY | 3-Year Limited |











ORDERING GUIDE EX: PLC230-30K-BK-12V

| PLC230 | | | |
|--------|--------------------|---------------------------|---------------------|
| MODEL | COLOR TEMP | FINISH | VOLTAGE |
| | 30K - 3000K | BK - Black SI - Silver | 12V - 12V DC |
| | | | |


JOB NAME: LOCATION: QUOTE/REF#:

PLC-230 is a sleek, ultra slim LED puck light suitable for surface mount applications. This dimmable LED puck light delivers 240 lumens at 3W in 3000K. Its small form factor and low profile design makes it easy to setup and install. Adding this LED puck light to any design space or functional piece instantly gives it an upgrade with spot or focused lighting. Ideal for under cabinet lighting, shelves, counter and display illumination.


FEATURES

- Surface applications
- 240 Lumens
- 90+ CRI
- 20W Halogen replacement
- Low profile design
- Dimmable with CORE Lighting dimmable transformers
- Splitter available for multi-puck installation

| FINISH | CRI | LUMEN | |
|--------|-----|-------|--|
| ВК | 90+ | 240 | |
| SI | 90+ | 240 | |



DIMENSIONS




PLC-230 3.0W Ultra Slim LED Puck Light



COMPATIBLE ACCESSORIES


4-WAY SPLITTER I Splits a connection into 4

PLC-4AP-MT 1 to 4 splitter for multi-puck installation



6-WAY SPLITTER I Splits a connection into 6

PLC-6AP-MT 1 to 6 splitter for multi-puck installation






COMPATIBLE DIMMABLE TRANSFORMERS

HIGH PERFORMANCE (MLV)





| PSDH SERIES | CLASS 2 | LXWXH |
|---------------|---------|------------------------|
| PSDH-48W-24V | YES | 11.25" X 3.37" X 3.25" |
| PSDH-96W-24V | YES | 11.25" X 3.37" X 3.25" |
| PSDH-288W-24V | YES | 14.25" X 8.43" X 4.43" |



* 277 VERSIONS AVAILABLE, PLEASE CONSULT FACTORY

TRIAC DIMMING ELECTRONIC







| PSDT SERIES | CLASS 2 | LXWXH |
|------------------|---------|-----------------------|
| | | |
| PSDT-20W-12V | YES | 6.1" X 2.12" X 0.79" |
| PSDT-20W-24V | YES | 6.1" X 2.12" X 0.79" |
| PSDT-40W-12V | YES | 7.0" X 2.4" X 0.95" |
| PSDT-40W-24V | YES | 7.0" X 2.4" X 0.95" |
| PSDT-60W-12V | YES | 7.1" X 2.36" X 1.38" |
| PSDT-60W-24V | YES | 7.1" X 2.36" X 1.38" |
| PSDT-96W-24V-JB | YES | 9.06" X 2.76" X 1.82" |
| PSDT-120W-12V-JB | NO | 8.92" X 3.0" X 1.85" |
| PSDT-150W-24V-JB | NO | 8.92" X 3.0" X 1.85" |
| PSDT-200W-24V-JB | NO | 8.92" X 3.0" X 1.85" |
| | | |

