


LSP-80RGB 8.8W Indoor Color-changing LED Strip

CORE
ARCHITECTURAL
LIGHTING

JOB NAME: _____
LOCATION: _____
QUOTE/REF#: _____



LSP80-RGB is an indoor rated color-changing LED strip that provides a full spectrum of color changing schemes. The LEDs' combined full color spectrum of the RGB light array produces more powerful color options that's sure to please even the most discerning lighting designer. Suitable for residential, commercial, hospitality and architectural lighting applications.


SPECIFICATIONS

INPUT VOLTAGE	24V DC
POWER CONSUMPTION	8.8W per foot
LUMEN OUTPUT	720 Lumens per foot
NO. OF LEDs	36 LEDs per foot
BEAM ANGLE	120°
CRI	90+
DIMMING	Through RGB controller
MAXIMUM RUN LENGTH	20 Feet
FIELD CUTTABLE	Every 3.9 in (100MM)
IP RATING	IP45 dry location (indoor)
LUMEN MAINTENANCE	50,000 hrs.
OPERATING TEMPERATURE	-40°F(-40°C)~+140°F(+60°C)
BINNING	1.5 Step Macadam Elipse
CERTIFICATIONS	UL listed
DIMENSIONS	0.78" x 0.08 (width x height)

FEATURES

- 8.8W per Foot
- 720 Lumens
- 90+ CRI
- Two rows of high-output diodes
- 20 Feet Maximum Run Length
- Field cuttable
- Ideal for color-changing accent lighting
- Color changing + white
- UL Listed, Title 24 JA8 compliant
- Dimmable with RGBW controllers

RGB COLOR SPECTRUM



LSP-80RGB

8.8W Indoor Color-changing LED Strip



STANDARD ORDERING CODE


Model	Color Temp	Length	Voltage	Profile
LSP-80	RGB RGB Color-Changing	16 16.4 Ft. 100 100 Ft. 'XX per Ft.	24 24 Volts	² See p3 for options

NOTE:


- 1 = Custom length per Ft.
Cuttable every 1"
- 2 = Custom color finishes require
powder coating. Allow 7 days
lead time.

LSP-80RGB 8.8W Indoor Color-changing LED Strip


COMPATIBLE ALUMINUM PROFILES




ALU-DS100 **SURFACE MOUNT**
LENGTHS 39 3/8" 78 7/8" 96"
LENS Clear and Frosted
FINISH Anodized Aluminum




ALP-90 **SURFACE MOUNT**
LENGTHS 48" and 96"
LENS Frosted
FINISH Anodized Aluminum




ALP-140 **SURFACE / SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum




ALP-160 **SURFACE / SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum




ALP-200 **SURFACE / SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum




ALP-245 **SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum




ALP-230N **SURFACE / SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum



ALP-230RN **RECESSED**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum




ALP-310N **SURFACE / SUSPENSION**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum



ALP-330RN **RECESSED**
LENGTHS 49.25" , 98.5"
LENS Frosted
FINISH Anodized Aluminum


LSP-80RGB 8.8W Indoor Color-changing LED Strip

COMPATIBLE RGBW CONTROLLERS



RGB-CT600

INPUT VOLTAGE	5V DC, 1A
OUTPUT SIGNAL	RF 2.4GHz + DMX512
CONTROL	4 ZONES
WORKING TEMP	-30°C ~ 55°C
WEIGHT (gross)	370g




RGB-SDE3

INPUT POWER	6V DC 0.6A
OUTPUT SIGNAL	DMX512 (x2)
PROGRAMMABILITY	PC, MAC, Tablet, Smartphone
AVAILABLE COLORS	Black / White
CONNECTIONS	USB, Ethernet, RS232, Clock, 8dry contact ports, 5V output relay
MEMORY	microSD card
WORKING TEMP	-10°C ~ 45°C
MOUNTING	Single or double gang wall socket
WEIGHT (gross)	247g


LSP-80RGB 8.8W Indoor Color-changing LED Strip

COMPATIBLE RGBW CONTROLLERS



RGB-DMX4C

INPUT	12V - 24V DC
OUTPUT CURRENT	8A X 4CH
OUTPUT POWER	240W(12V), 720W (24V)
OUTPUT CHANNELS	3 or 4 selectable



RGB-DMX5C-XLR

INPUT	12V-24V-36V DC
OUTPUT CURRENT	8A X 5CH

LSP-80RGB

8.8W Indoor Color-changing LED Strip

COMPATIBLE TRANSFORMERS



PSHK SERIES NON-DIMMING WITH JUNCTION BOX

PSHK-30W-24V-UNV	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V-UNV	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V-UNV	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V-UNV		10.24" X 4.06" X 1.81"
PSHK-200W-24V-UNV		10.24" X 4.06" X 1.81"
PSHK-300W-24V-UNV		10.94" X 4.25" X 1.81"