

IGUFR SERIES

In-Ground Linear Uplight With Frosted Diffuser

JOB NAME: _____
LOCATION: _____
QUOTE/REF#: _____






In-grade linear uplight ideally suited for in-ground/recessed installations in concrete or lawn for wall wash and ground mounted signs and linear objects. DMX controlled RGB colour changes available as well as dimmable white light.

SPECIFICATIONS

HOUSING	Extruded Anodized Aluminum
END CAPS	Die-Cast Aluminum
GASKET	Silicone Rubber
COVER	Tempered Glass
TOP COVER FRAME	Stainless Steel 316
INPUT VOLTAGE	120~277V AC 24VDC option available
IP RATING	1000 lbs (500 kgs)
MAX LOAD	-20°C~45°C
AMBIENT TEMPERATURE	3000K / 4000K / 5000K
CCT	90 CRI
CRI	50,000
LUMEN MAINTENANCE	30K - 1080Lm
LUMENS	40K - 1200Lm 60K - 1320Lm

FEATURES

- 1080 ~ 1320 Lumens
- 120~277V AC
- Also available in 24V (requires transformer)
- 98° beam spread
- MAX LOAD: 1000 lbs (500 kgs)
- Built-in Driver
- Stainless Steel Frame
- Clear Tempered Glass
- Stainless Steel Frame
- Recessed Housing Included

	COLOR TEMP	CRI	LUMENS
	3000K	80	432
	4000K	80	432
	5000K	80	432



IGUFR SERIES

In-Ground Linear Uplight With Frosted Diffuser

STANDARD ORDERING CODE

Model	Length	Color Temp	Voltage	Control
IGUFR	20 20 IN	30K 3000K	24VDC 24 Volts	NDM No Dimming
	40 40 IN	40K 4000K	UNV 120V-277V	D10 0-10V Dimming
		50K 5000K		

DIMENSIONS

