



#### JOB NAME: \_\_\_\_\_\_ LOCATION: \_\_\_\_\_ QUOTE/REF#: \_\_\_\_\_

The ALU-CN is an Architectural-grade LED extrusion designed for surface / corner mount applications and can fit linear LED strips up to 12mm (0.48") wide. Made from high quality aluminum and manufactured with a patented frosted diffuser for maximum lumen output and wider beam distribution.

### SPECIFICATIONS

ТҮРЕ	Surface mount					
AVAILABLE LENGTHS	39 <sup>3/8"</sup>   78 <sup>7/8"</sup>   96"					
FINISH	Anodized Aluminum					
LENS OPTIONS	Frosted   Clear					
CHANNEL	ALU-CN					
LENS (SOLD SEPARATELY)	ALU-LN50-FR (frosted) ALU-LN50-CL (clear)					
END CAP	ALU-CN-EC					
MOUNTING CLIPS	ALU-CN-M					
WEIGHT	1.5 lbs					

Compatible with LED strips up to 12mm (0.48") wide. LED tape light sold separately. Clear and Frosted Lens diffuser sold separately

2 (two) end caps included with every channel.


Custom color finishes available (powder-coating).



### FEATURES

- Customizable
- Durable, anodized aluminum
- Protects LED systems from dust and other elements
- Slim, low profile design
- Dissipates heat from LED, prolonging its lifetime

# DIMENSIONS





### STANDARD ORDERING CODE (CHANNEL)

Model	Length	Finish
ALUCN	<b>39</b> 39.375 <sup>°</sup>	<b>SI</b> Silver
	<b>78</b> 78.875"	<b>BK</b> Black
	<b>96</b> 96″	<b>CU</b> Custom (powder-coat)

### STANDARD ORDERING CODE (LENS)

Model	Lens Type	Length
ALULN50	<b>FR</b> Frosted	<b>39</b> 39.375″
	<b>CL</b> Clear	<b>78</b> 78.875″
		<b>96</b> 96″

**NOTE:** Custom color finishes require powder coating. Allow 7 days lead time.

## **COMPATIBLE ACCESSORIES**

ALU-LN50	Plas	stic	Lens	5 (	sol	d	SE	pa	arate	ly)
							,		,	

 TYPE
 FR (frosted) | CL (clear)

 LENGTHS
 39<sup>3/8°</sup> | 78<sup>7/8°</sup> | 96″



ALU-CN | Aluminum Channel MOUNTING Surface

**LENGTHS** 39<sup>3/8°</sup> | 78<sup>7/8°</sup> | 96"

ALU-CN-EC | End Cap

\*Two end caps included with every channel

ALU-CN-M | Metal Mounting Clips















#### Indoor

LSM-15 1.5W/Ft., 120 Lumens

LSM-25 2.2W/Ft., 185 Lumens

LSM-30 3.0W/Ft., 250 Lumens

LSM-35WD 3.6W/Ft., Auto Warm Dim

LSM-40HF 4.0W/Ft., 440 Lumens

LSM-45 4.4W/Ft., 370 Lumens

LSP-50 4.4W/Ft., 380 Lumens

LSM-55 5.5W/Ft., 500+ Lumens

LSM-55MX 5.5W/Ft., 500+ Lumens

#### Outdoor

LSMW-15 1.5W/FT, 120 Lumens

**LSMW-30** 3.0W/FT, 250 Lumens Indoor Color-changing

LSP-20-RGB 2.2W/FT

LSP-50-RGB 4.4W/FT

LSP-50-RGB-DX 4.4W/FT Digital

