



SPECIFICATIONS

ТҮРЕ	Surface mount
AVAILABLE LENGTHS	39 ^{3/8"} , 78 ^{7/8"} and 98"
FINISH	Anodized Silver / Black
LENS OPTIONS	Frosted / Clear
CHANNEL	ALU-SF
LENS (SOLD SEPARATELY)	ALU-LN50-FR (frosted)
	ALU-LN50-CL (clear)
END CAP	ALU-SF-EC
MOUNTING CLIPS	ALU-SC-M

Compatible with LED strips up to 12mm (0.48") wide.

LED tape light sold separately.

Clear and Frosted Lens diffuser sold separately

2 (two) end caps included with every channel.

Custom color finishes available (powder-coating).

98" profile NOT available in black




JOB NAME:	
LOCATION:	
QUOTE/REF#:	

The **ALU-SF** is an architectural-grade LED extrusion designed for linear LED strips up to 12mm (0.48") wide. Made from high quality aluminum, these extrusions provide superior thermal management for LED strips and prolong the lighting system's lifespan. Manufactured with a patented frosted diffuser for maximum lumen output and wider beam distribution.


FEATURES

- Customizable
- Durable, anodized aluminum
- Protects LED systems from dust and other elements
- Slim, low profile design
- Dissipates heat from LED, prolonging its lifetime

DIMENSIONS



DIMENSIONS with mounting clip





STANDARD ORDERING CODE (CHANNEL)

Model	Length	Finish
ALUSF	39 39.375 [°]	SI Silver
	78 78.875"	BK Black (39" & 78" ONLY
	98 98″	CU Custom (powder-coat)

STANDARD ORDERING CODE (LENS)

Model	Length
ALULN50	39 39.375 [°]
	78 78.875″
	98 98"

NOTE: Custom color finishes require powder coating. Allow 7 days lead time.

98" profile NOT available in black





ALU-LN50 | Plastic Lens (sold separately)

 TYPE
 FR (frosted) | CL (clear)

 LENGTHS
 39^{3/8*}, 78^{7/8*} and 98*





ALU-SF | Aluminum Channel

MOUNTING Surface LENGTHS 39^{3/8*}, 78^{7/8*} and 98"

ALU-SF-EC | End Cap

*Two end caps included with every channel

ALU-SC-M | Metal Mounting Clips





150 West Carob Street, Compton, California 90220 info@corelightingusa.com | www.corelightingusa.com T: 888.737.9192 | F: 888.789.4643





Indoor

LSM-15 1.5W/Ft., 120 Lumens

LSM-25 2.2W/Ft., 185 Lumens

LSM-30 3.0W/Ft., 250 Lumens

LSM-32CB 3.2W/Ft., 292 Lumens

LSM-35 3.0W/Ft., 290 Lumens

LSM-35WD 3.6W/Ft., Auto Warm Dim

LSM-40HF 4.0W/Ft., 440 Lumens

LSM-45 4.4W/Ft., 370 Lumens

LSP-50 4.4W/Ft., 380 Lumens

LSM-55 5.5W/Ft., 500+ Lumens

LSM-55MX 5.5W/Ft., 500+ Lumens

LSM-55WD 5.5W/Ft., Auto Warm Dim

LSM-75HF 7W/Ft., 784 Lumens

Outdoor

LSMW-15 1.5W/FT, 120 Lumens

LSMW-30 3.0W/FT, 250 Lumens

Color-changing

LSP-20-RGB 2.2W/FT

LSP-50-RGB 4.4W/FT

LSP-50-RGB-DX 4.4W/FT Digital

LSP-52-RGBW

LSM-55-RGBW 5W/FT

LSP-70-RGBWW 7W/FT