

SPECIFICATION SHEET



SPECIFICATIONS

AVAILABLE LENGTHS49.25', 84' and 98.5'FINISH OPTIONSWHITE BLACK SILVERLENS OPTIONSFrostedCHANNELALP-60RLENSALP-60R-LNEND CAPALP-60R-EC	ТҮРЕ	Recessed mount
LENS OPTIONS Frosted CHANNEL ALP-60R LENS ALP-60R-LN	AVAILABLE LENGTHS	49.25 ", 84" and 98.5"
CHANNEL ALP-60R LENS ALP-60R-LN	FINISH OPTIONS	WHITE I BLACK I SILVER
LENS ALP-60R-LN	LENS OPTIONS	Frosted
	CHANNEL	ALP-60R
END CAP ALP-60R-EC	LENS	ALP-60R-LN
	END CAP	ALP-60R-EC

Compatible with LED strips up to **11mm (0.44in) wide.** LED tape light sold separately. Frosted Lens diffuser included (1 with every channel) 2 (two) end caps included with every channel. Custom color finishes available (powder-coating).

ORDERING CODE

Model	Length	Lens	Light Engine	Finish
ALP-60R	49 - 49.25 in 84 - 84 in	FR - Frosted	See P. 3	WH White
	98 - 98.5 in			BK Black
				SI Silver
				CII

Custom (powder-coat)


JOB NAME:	
LOCATION:	
QUOTE/REF#:	

The **ALP-60R** is a recessed architectural grade LED extrusion profile designed for linear LED strips up to **11mm (0.44in)** wide. Made from high quality anodized aluminum, this extrusion provides superior thermal management for higher wattage LED strips and prolong the lifespan of the lighting system. This recessed mount profile comes with a patented frosted diffuser lens for maximum lumen output and wide beam distribution. The **ALP-60R** profile helps protect LED's from dust and other undesirable elements, which can shorten the LEDs life. They are also an elegant design solution for any space.

FEATURES

- Customizable
- Durable, anodized aluminum
- Protects LED systems from dust and other elements
- Suitable for recessed installations / applications.
- Dissipates heat from LED, prolonging its lifetime

DIMENSIONS







ASSEMBLY

ALP-60R-LN | Plastic Lens

TYPEFR (frosted)LENGTHS49.25" and 98.5"



ALP-60R | Aluminum Channel

MOUNTING Surface LENGTHS 49.25" and 98.5"



ALP-60R-EC | End Cap

*Two end caps included with every channel





COMPATIBLE LED STRIPS

Indoor	Outdoor	Indoor Color-changing
LSM-15 1.5W/FT, 120 Lumens	LSMW-15 1.5W/FT, 120 Lumens	LSP-20-RGB 2.2W/FT
LSM-25 2.2W/FT, 185 Lumens	LSMW-30 3.0W/FT, 250 Lumens	LSP-50-RGB 4.4W/FT
LSM-30 3.0W/FT, 250 Lumens		LSP-50-RGB-DX 4.4W/FT Digital
LSM-35WD 3.6W/FT, Auto Warm Dim		
LSM-40HF 4.0W/FT, 440 Lumens		
LSM-45 4.4W/FT, 370 Lumens		
LSP-50 4.4W/FT, 380 Lumens		
LSM-55 5.5W/FT, 500+ Lumens		
LSM-55MX		