

# SPECIFICATION SHEET



JOB NAME:	
OOD IV WIL.	
LOCATION:	
OLIOTE/DEE/	
QUOTE/REF#:	

The **ALP-70** is an Architectural Grade LED extrusion profile designed for linear **LED strips up to 14mm** wide. Made from high quality aluminum, these extrusions provide superior thermal management for higher wattage LED strips and prolong the lifespan of your lighting system. This surface mount profile is manufactured with a patented frosted diffuser for maximum lumen output and wide beam distribution. These aluminum profiles are an elegant design solution for any space.


- Compatible with LED strips up to 0.55in | 9/16 in | 14mm.
- Customizable lengths
- Low profile design
- Dissipates heat from LED strips.
- Remote mounted low-voltage power supply sold separately
- Includes standard frosted lens with each profile

#### **SPECIFICATIONS**

TYPE	Surface mount	
AVAILABLE LENGTHS	49.25", 84" and 98.5"	
FINISH	Black   Silver	
LENS OPTIONS	Standard frosted lens included	

- \* Frosted lens included with every channel
- \* Two (2) end caps included with every channel.
- \* Custom color finishes available (powder coating).

#### **DIMENSIONS**



### **ORDERING CODE**

			10.1	
Model	Length	Lens	Light Engine	Finish
ALP-70	<b>49 -</b> 49.25 in <b>84</b> - 84 in <b>98 -</b> 98.5 in	FR - Frosted	See P. 3	BK Black SI Silver CU (ustom (powder-coat)













## **COMPONENTS | ACCESSORIES**

ALP-70 | Aluminum Channel

**MOUNTING** Surface

LENGTHS 49.25", 84" and 98.5"



ALP-70LN | Lens Cover

**TYPE** Frosted (included)

LENGTHS 49.25", 84" and 98.5"



ALP-70EC | End Cap

Two end caps included with every profile



ALP-70CL | Metal Mounting Clips


Two end caps included with every profile






ALP-70-BKT-ADJ | Adjustable Bracket

\* optional item (sold separately)






ALP-70-ASB | Adjustable Bracket

\* optional item (sold separately)







### **TAPE LIGHT - CHANNEL COMPATIBILITY**

	INDOOR LED STRIPS		OUTDOOR LED STRIPS		RGB & RGBW
Ø	LSM-15 I 1.5W / FT.   120 Lumens	Ø	LSMW-15 I 1.5W / FT.   120 Lumens	Ø	LSP-20RGB   2.2W / FT.   82 Lumens
<b>⊘</b>	LSM-25   2.2W / FT.   185 Lumens	Ø	LSMW-25   2.2W / FT.   185 Lumens	<b>⊘</b>	<b>LSP-50RGB  </b> 4.4W / FT.   165 Lumens
<b>Ø</b>	LSM-30   3.0W / FT.   250 Lumens	<b>⊘</b>	LSMW-30   3.0W / FT.   250 Lumens		LSP-80RGB   8.8W / FT.   720 Lumens
<b>Ø</b>	LSM-45   4.4W / FT.   370 Lumens	Ø	LSMW-40HF   4.0W / FT.   440 Lumens	<b>(</b>	LSP-50RGBW I 4.4W / FT.   165 Lumens
<b>⊘</b>	<b>LSM-40HF I</b> 4.0W / FT.   440 Lumens		LSMW-60   6.0W / FT.   500 Lumens		LSP-80RGBW   8.8W/FT.   720 Lumens
<b>⊘</b>	LSM-55 I 5.5W / FT.   500+ Lumens				
<b>Ø</b>	LSP-50   4.4W / FT.   380 Lumens				
<b>⊘</b>	LSM-60   6.0W / FT.   500 Lumens				
<b>⊘</b>	LSM-60MX   6.0W / FT.   500 Lumens				
	LSP-80   8.8W / FT.   720 Lumens				
	<b>LSM-70HF I</b> 6.6W / FT.   698 Lumens				
	<b>LSM-90HF I</b> 7.9W / FT.   930 Lumens				