


## SPECIFICATION SHEET

JOB NAME: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 QUOTE/REF#: \_\_\_\_\_



The **ALP-210RN** is a recessed, Architectural Grade LED extrusion profile designed for linear LED strips up to 23mm wide. Made from high quality aluminum, these extrusions provide superior thermal management for higher wattage LED strips and prolong the overall lifetime of your lighting system. The **ALP-210RN** is manufactured with a patented frosted diffuser for maximum lumen output and wide beam distribution. The **ALP-210RN** also helps protect LED's from dust and other undesirable elements, which can shorten the lifetime of the LED.

### FEATURES

- Customizable
- Ideal for recessed applications
- Durable, military grade aluminum
- Protects LED systems from dust and other elements
- Dissipates heat from LED, prolonging its lifetime

### SPECIFICATIONS

TYPE	Recessed mount
AVAILABLE LENGTHS	49.25" and 98.5"
FINISH	Anodized Silver
LENS OPTIONS	Frosted

Compatible with LED strips up to 0.93" / 15/16" / 23.5mm wide.

LED tape light sold separately.

Remote mounted low voltage power supply sold separately.

Power supplies available in 120V and 277 options.

### COMPONENTS


PROFILE	ALP-210RN
LENS	ALP-210RN-LN
END CAP	ALP-210RN-EC
RECESSED BRACKETS	ALP-210RN-RE

Frosted lens included with each channel.

Two (2) end caps included with every channel.

Two (2) recessed brackets included with every channel.

Custom color finishes available (powder coating).



### ORDERING GUIDE EX: ALP210RN-49-FR


ALP-210RN	SIZE	LENS	LIGHT ENGINE
MODEL			
	49 - 49.25 Inches 98 - 98.5 Inches	FR - Frosted Lens	See p.5 for compatible tape lights

## COMPONENTS | ACCESSORIES

### ALP-210RN-LN | Plastic Lens

**TYPE** FR (frosted)


**LENGTHS** 49.25" and 98.5"



### ALP-210RN | Aluminum Profile


**MOUNTING** Recessed

**LENGTHS** 49.25" and 98.5"




### ALP-210RN-EC | End Cap

\*Two end caps included with every profile




### ALP-210RN-RE | N type bracket

\*Two recessed brackets included with every profile




## OPTIONAL ACCESSORIES (SOLD SEPARATELY)


ALP-210RN-L90W | L connector (OUTSIDE)




ALP-210RN-L90N | L connector (INSIDE)



ALP-210RN-L90 | L connector (SIDE)




ALP-210RN-T90 | T connector




## OPTIONAL ACCESSORIES (SOLD SEPARATELY)


ALP-210RN-X90 | X connector



ALP-210RN-SC | Seamless connector




ALP-210RN-RB | Butterfly clip




## MOUNTING OPTIONS



**N TYPE CLIP**  
ALP-210RN-RE



**BUTTERFLY TYPE CLIP**  
ALP-210RN-RB



## TAPE LIGHT - CHANNEL COMPATIBILITY

	INDOOR LED STRIPS		OUTDOOR LED STRIPS		RGB & RGBW
✓	LSM-15   1.5W / FT.   120 Lumens	✓	LSMW-15   1.5W / FT.   120 Lumens	✓	LSP-20RGB   2.2W / FT.   82 Lumens
✓	LSM-25   2.2W / FT.   185 Lumens	✓	LSMW-25   2.2W / FT.   185 Lumens	✓	LSP-50RGB   4.4W / FT.   165 Lumens
✓	LSM-30   3.0W / FT.   250 Lumens	✓	LSMW-30   3.0W / FT.   250 Lumens	✓	LSP-80RGB   8.8W / FT.   720 Lumens
✓	LSM-45   4.4W / FT.   370 Lumens	✓	LSMW-60   6.0W / FT.   500 Lumens	✓	LSP-50RGBW   4.4W / FT.   165 Lumens
✓	LSM-55   5.5W / FT.   500+ Lumens			✓	LSP-80RGBW   8.8W / FT.   720 Lumens
✓	LSP-50   4.4W / FT.   380 Lumens				
✓	LSM-60   6.0W / FT.   500 Lumens				
✓	LSM-60MX   6.0W / FT.   500 Lumens				
✓	LSP-80   8.8W / FT.   720 Lumens				
✓	LSM-70HF   6.6W / FT.   698 Lumens				
✓	LSM-90HF   7.9W / FT.   930 Lumens				