

SPECIFICATION SHEET



SPECIFICATIONS

TYPE	Surface / suspended mount			
AVAILABLE LENGTHS	49.25" and 98.5"			
FINISH	Anodized Silver			
LENS OPTIONS	Frosted			
Compatible with LED strips up to 1.0" / 2	5mm wide.			
LED tape light sold separately.				
Remote mounted low voltage power supply sold separately.				
Power supplies available in 120V and 277 options.				




The ALP-190 is an Architectural Grade LED extrusion profile designed for linear LED strips up to 25mm wide. Made from high quality aluminum, these extrusions provide superior thermal management for higher wattage LED strips and prolong the overall lifetime of your lighting system. The ALP-190 is manufactured with a patented frosted diffuser for maximum lumen output and wide beam distribution. The ALP-190 also helps protect LED's from dust and other undesirable elements, which can shorten the lifetime of the LED.

FEATURES

- Customizable
- Ideal for surface mount applications
- Durable, military grade aluminum
- Protects LED systems from dust and other elements
- Dissipates heat from LED, prolonging its lifetime

COMPONENTS

PROFILE	ALP-190		
LENS	ALP-190-LN		
END CAP	ALP-190-EC		
*SUSPENSION KIT	ALP-CS12		
**CANOPY KIT	ALP-CF		
Frosted lens included with each channel.			
Two (2) end caps included with every channel.			
Custom color finishes available (powder coating).			
*Required for suspension applications (sold separately)			
** Optional for suspended applications (sold separately)			
	* ***		















ORDERING GUIDE

ALP-190			
MODEL	SIZE	LENS	LIGHT ENGINE
	49 - 49.25 Inches 98 - 98.5 Inches	FR - Frosted Lens	See p.3 for compatible tape lights



COMPONENTS I ACCESSORIES

ALP-190-LN | Plastic Lens

TYPE	FR (frosted)	FR (frosted)		
LENGTHS	40.25" and 08.5"			



ALP-190 | Aluminum Profile

MOUNTING	Surface / suspended
LENGTHS	49 25" and 98 5"



ALP-190-EC | End Cap

*Two end caps included with every profile



ALP-CS12 | Suspension Kit

*Required for suspension option (sold separately)





ALP-190 Surface / Suspended Mount LED Profile



TAPE LIGHT - CHANNEL COMPATIBILITY

	INDOOR LED STRIPS		OUTDOOR LED STRIPS		RGB & RGBW
Ø	LSM-15 I 1.5W / FT. 120 Lumens	Ø	LSMW-15 1.5W / FT. 120 Lumens	Ø	LSP-20RGB 2.2W / FT. 82 Lumens
Ø	LSM-25 2.2W / FT. 185 Lumens	Ø	LSMW-25 2.2W / FT. 185 Lumens	Ø	LSP-50RGB 4.4W / FT. 165 Lumens
\bigcirc	LSM-30 3.0W / FT. 250 Lumens	Ø	LSMW-30 I 3.0W / FT. 250 Lumens	Ø	LSP-80RGB 8.8W / FT. 720 Lumens
\bigcirc	LSM-45 I 4.4W / FT. 370 Lumens	Ø	LSMW-60 I 6.0W / FT. 500 Lumens	Ø	LSP-50RGBW 4.4W / FT. 165 Lumens
Ø	LSM-55 5.5W / FT. 500+ Lumens			3	LSP-80RGBW I 8.8W / FT. 720 Lumens
\bigcirc	LSP-50 4.4W / FT. 380 Lumens				
\bigcirc	LSM-60 I 6.0W/FT. 500 Lumens				
Ø	LSM-60MX I 6.0W / FT. 500 Lumens				
Ø	LSP-80 8.8W / FT. 720 Lumens				
Ø	LSM-70HF I 6.6W / FT. 698 Lumens				
Ø	LSM-90HF I 7.9W / FT. 930 Lumens				