


SPECIFICATION SHEET

JOB NAME:	
JOD NAME.	
LOCATION:	
OLIOTE/DEE/	
QUOTE/REF#:	



LSH-50N is a dimmable flexible LED strip capable of delivering up to 295 Lumens of light output per foot. These flexible LED lights is cuttable every 12", and produces a 120° light beam spread. These strips are great for common commercial and residential lighting applications such as under cabinet and cove lighting, shelf and display lighting, interior signage, exhibit lighting and more. Flux LED series are bright eco-friendly LED strips.

SPECIFICATIONS

INPUT VOLTAGE 120V DC **POWER CONSUMPTION** 4.4W per foot

LUMEN OUTPUT 275 Lumens per foot (30K) 295 Lumens per foot (40K)

NO. OF LEDs 19 LEDs per foot

 BEAM ANGLE
 120°

 CRI
 90+

DIMMING Compatible with CL dimmers

MAXIMUM RUN LENGTH 150 Feet FIELD CUTTABLE Every 12 in

IP RATING IP65 wet location (outdoor)

LUMEN MAINTENANCE 50,000 hrs.

OPERATING TEMPERATURE
-40°F(-40°C)~+140°F(+60°C)

BINNING
1.5 Step Macadam Elipse

CERTIFICATIONS
UL listed, TITLE 24 JA8

DIMENSIONS
0.55" x 0.25 (width x height)

FEATURES

- 4.4W per Foot
- 19 LEDs per ft.
- 120V No Transformer Required
- California TITLE 24 JA8 compliant
- Suitable for accent or ambient lighting
- Multiple CCT options available
- Superior COLOR RENDERING INDEX (CRI)
- UL Listed
- Dimmable with CL dimmers

4.4W PER FT.	120V	OUTDOOR	25,000 Howrs	DIMMABL
		OUTDOOK	II 9 W K S	DIMINABLE







 COLORTEMP	CRI	LUMEN/FT
3000K	90+	275
4000K	90+	295
BLUE	90+	295

LSH-50N 4.4W 120V Outdoor Flexible LED Strip



STANDARD ORDERING CODE

Model Color Temp Length Voltage

LSH-50N 30K - 3000K **50** - 50 Ft. **120V** - 120V DC **40K** - 4000K **150** - 150 Ft.

BL - BLUE

CUSTOMIZED LENGTH ORDERING CODE

Model Color Temp Length Voltage

model color ramp zangin ratingo

LSH-50N 30K - 3000K **XX** - Custom Length **120V** - 120V DC

40K - 4000K

LSH-50N 4.4W 120V Outdoor Flexible LED Strip



COMPATIBLE ACCESSORIES



ALUMINUM CHANNEL

LSH50N-AC2 2" Aluminum Channel
LSH50N-AC36 36" Aluminum Channel
FINISH Anodized Aluminum

LENS N/A



PLASTIC CHANNEL

LSH50N-PC2 2" Plastic Channel **LSH50N-PC36** 36" Plastic Channel

FINISH Plastic
LENS N/A



POWER CORD ADAPTOR

LSH50N-PCA60 60" Power Cord



CLEAR MOUNTING CLIPS

LSH50N-CL *1 pair included



EXTENSION LINK CABLE

LSH50N-LNK2 2" Extension Cable **LSH50N-LNK8** 8" Extension Cable



MINI COUPLING

LSH50N-MC Seamless Connector