

ARTIC-MX

MINI COLOR TUNING WALL WASHER

Project _____

Location _____

Quote/ Ref # _____

The **Artic-MX** is an outdoor, high performance, LED wall washer featuring an articulating design which allows for the uniform illumination of curved facades, walls and circular columns. Individually aimed and addressable compact modules provide flexibility in creating seamless facade highlights. Available in various beam angles and elliptical optics. The adaptability of the Artic makes it a great fit for the most challenging applications



SPECIFICATIONS

POWER CONSUMPTION	7W per 6.6 in per module
LUMEN OUTPUT	500 Lumens/ module (RGB)
CONTROL	DMX
CRI	90+
COLOR TEMPERATURE	27K-5000K
MAXIMUM RUN LENGTH	Linkable up to 18 individual modules
OPERATING VOLTAGE	24V DC
OPERATING FREQUENCY	50/ 60 Hz
STORAGE TEMPERATURE	-30°C to 60°C
OPERATING TEMPERATURE	-40°C to 60°C
BEAM ANGLE OPTIONS	10°/15°/ 30°/10° X 50°/ 20° X 40°
IP RATING	IP67 Outdoor/ Wet Location
LUMEN MAINTENANCE	50,000 Hrs.

FEATURES

- 140 Lumens per module (RGB)/ 240 Lumens per module (RGBW)
- Modules are individually addressable
- Can daisy chain up to 3 groups of 6 (Max. 18 modules)
- Proprietary Optical Technology
- DMX Ready
- Adjustable Mounting Bracket
- Facade Wall Washing
- Graze Lighting
- Signage




MODEL	MODULES	COLOR TEMP	OPTICS	FINISH	VOLTAGE	OPTIONS
ARC	1 1 Module	MX-22K/40K 2200-4000K	10 10°	BK Black	24V 24 Volts DC	FLV Flat Louvre <small>*Product ships with Flat Louvre unless specified</small>
	3 3 Modules	MX-27K/50K 2700-5000K	15 15°	WH White		ALV Angled Louvre
	6 6 Modules		30 30°			SDLV Standard Louvre
			1050 10° x 50°			
			2040 20° x 40°			

*Special order item— allow up to 4 weeks of lead time


ARTIC-MX

MINI COLOR TUNING WALL WASHER

DIMENSIONS




OPTICS




ACCESSORIES

FLAT LOUVRE (FLV)

* Product ships with Flat Louvre unless specified



ANGLED LOUVRE (ALV)





ARTIC-MX

MINI COLOR TUNING WALL WASHER

ACCESSORIES

STANDARD LOUVRE (SDLV)



CABLES

ARC-MX-LNK-10
ARC-MX-LNK-36
ARC-MX-LNK-72
10", 36", 72" LINK EXTENSION CABLE
*Sold Separately



ARC-MX-HWC-72
72" HARDWIRE CABLE
*Sold Separately




ARTIC-MX

MINI COLOR TUNING WALL WASHER

DMX CONTROLLERS


RGB CT600
MULTI-FUNCTION RGBW WALL CONTROLLER

INPUT VOLTAGE 5V DC, 1A
OUTPUT SIGNAL RF 2.4GHZ + DMX512
CONTROL 4 ZONES
COLOR OPTIONS Black/ White
WORKING TEMP -20°C ~ 40°C
DIMENSIONS LxWxH (5.19"x7.08"x1.38")




RGB-SCW4
WiFi DMX WALL CONTROLLER

INPUT VOLTAGE 5 - 10V DC, 06A
OUTPUT SIGNAL DMX512 (x2)
PROGRAMMABILITY PC/ MAC
COLOR OPTIONS Black/ White
CONNECTIONS USB/ 8dry contact ports/ Open drain output (for relay)
MEMORY Built-In Flash
WORKING TEMP -10°C ~ 45°C
DIMENSIONS LxWxH (5.75"x4.17"x0.43")



RGB-SDE3
WiFi DMX WALL CONTROLLER

INPUT VOLTAGE 6V DC, 0.6A
OUTPUT SIGNAL DMX512 (x2)
PROGRAMMABILITY PC/ MAC/ Tablet/ Smartphone
COLOR OPTIONS Black/ White
CONNECTIONS USB/ Ethernet/ RS232/ CLock/ 8dry contact ports/ 5V output relay
MEMORY MicroSD Card
WORKING TEMP -20°C ~ 40°C
DIMENSIONS LxWxH (5.75"x4.17"x0.43")



COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES
NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"

