

PSDE-96W-24V-UNV-DALI-2-DT8

96W CONSTANT-VOLTAGE DALI-2 DIMMING LED DRIVER

Project _____
Location _____
Quote/ Ref # _____

PSDE-96W-24V-UNV-DALI-2-DT8 is a constant-voltage DALI-2 DT8 dimming driver suitable for LED lighting systems. Manufactured with an advanced patented circuit board for smooth dimming operation with DALI systems. Built-in short circuit protection and 10% minimum load requirements make this driver one of the most efficient in the market.



SPECIFICATIONS

CLASS 2	Yes
WATTAGE	96W
INPUT VOLTAGE	120-277V
FREQUENCY	50/60 Hz
OUTPUT VOLTAGE	24V
OPERATING TEMPERATURE	-4°F(-20°C) ~ 122°F (50°)
DIMMING	DALI-2, DT8
CERTIFICATIONS	RoHS, UL Listed
DIMENSIONS	241.8 x 124 x 41.7mm (9.52 x 4.88 x 1.6") (LxWxH)

FEATURES

- Class 2
- DALI Driver/ Controller
- 96W
- Only 10% minimum load
- Flicker-free 0.1-100% dimming
- Dry/ Damp Environment

DIMENSIONS

INPUT	
INPUT VOLTAGE RANGE	100-277V AC
INPUT FREQUENCY RANGE	50/60 Hz
INPUT CURRENT (MAX.)	1.25A

OUTPUT	
OUTPUT VOLTAGE	24V
OUTPUT WATTAGE (MAX.)	96W
OUTPUT CURRENT (MAX.)	4A
MINIMUM LOAD	10%
MAXIMUM LOAD	100%

