

BRAVO

DIRECT/ INDIRECT LINEAR LED WALL MOUNT

Project

Location

Quote/ Ref #

The **Bravo** is an architectural LED luminaire featuring direct and indirect light distribution. Available in three output levels, delivering up to 704 lumens per foot, it includes a frosted lens for hotspot-free, uniform illumination—ideal for retail, office, educational, and commercial environments.



SPECIFICATIONS

INPUT VOLTAGE	24V
POWER CONSUMPTION	4W/ 5.5W/ 7W
LUMEN OUTPUT	704 Lm/ Ft. (30K)
BEAM ANGLE	180° (Downlight) 180° (Uplight)
COLOR TEMPERATURE	27K/ 30K/ 35K/ 40K/ 50K/ 65K
MAX RUN	Linkable up to 32 ft.
CRI	90
DIMMING	ELV, 0-10V, DALI and DMX
HOUSING	Extruded Aluminum
DRIVER	Remote
AMBIENT TEMPERATURE	-4° (-20°C) to 122° (50°C)
ENVIRONMENT	Dry/ Damp Locations
CERTIFICATIONS	UL Listed
LUMEN MAINTENANCE	50,000 Hrs.
WARRANTY	5-Year Limited

FEATURES

- Wall Mounted Luminaire
- Quick and Easy Installation
- Multiple CCT options available
- UL Listed (US and Canada)

LUMENS


CCT	WATTS (W/ FT.)	LM/FT (3000K)
L1	4W	440
L2	5.5W	529
L3	7W	704



MODEL	LENGTH	DOWNLIGHT	UPLIGHT	COLOR TEMP	FINISH	DIMMING
BVO	4 48"	DL1 4W	UL1 4W	27K 2700K	WH WHITE	ELV ELV Dimming
	8 96"	DL2 5.5W	UL2 5.5W	30K 3000K	CC Custom Color	DIM10 0-10 Dimming
	CU Custom Length	DL3 7W	UL3 7W	35K 3500K		DALI DALI Dimming
				40K 4000K		DMX DMX
				50K 5000K		
				65K 6500K		


DIRECT/ INDIRECT LINEAR LED WALL MOUNT

DIMENSIONS



ACCESSORIES

BVO-EC END CAP



BVO-MC MOUNTING CLIP

38mm x 15mm x 4.5mm (1.5" x 0.59" x 0.18")

