SAFIRE-35

3.5W DESIGNER SERIES LED TAPE LIGHT

UPDATED: 07.31.26

Project_____
Location_____
Quote/ Ref # _____

The **SAFIRE-35** — a high efficiency, indoor tape light designed to illuminate your space with unparalleled efficiency and versatility. The Safire Series utilizes the most technologically advanced LEDs in the market. Using only the top binned LEDs with a macadam ellipse 1.5 step binning procedure, Core Lighting can deliver the most efficient LED strip, with a longer life, higher CRI and higher R9 values. Choose from multiple CCT options ranging from 2200K to 5000K.

SPECIFICATIONS

POWER CONSUMPTION	3.5W per Ft.
LEDS/ FT.	53 LEDS per Ft.
LUMEN OUTPUT	333 ~ 460 Lumens per Ft.
CRI	95+
COLOR TEMPERATURE	22K/ 24K/ 27K/ 30K/ 35K/ 40K/ 50K
DIMMING	MLV, ELV, 0-10V and TRIAC
MAXIMUM RUN LENGTH	40 Ft.
CUTTABLE	Every 1.97 in (50mm)
BINNING	1.5-Step MacAdam Elipse
OPERATING VOLTAGE	24V DC
OPERATING TEMPERATURE	-22°F (-30°C) to +122°F (+50°C)
BEAM ANGLE	120°
RATING	Indoor
CERTIFICATIONS	UL Listed, California TITLE JA8
LUMEN MAINTENANCE	50,000 Hrs.

FEATURES

- 24V DC
- Continuous Run up to 40 Ft.
- 95+ CRI
- Custom length available every 1.97 in.
- Dimmable
- UL Listed (US and Canada)
- California TITLE 24 JA8 Compliant
- 7-Year Warranty*

* Only with compatible Core Lighting drivers

INDOOR 95+ CRI DIMMABLE 50,000 HRS JA8 TITLE 24 c UL us LISTED 7 YEAR WARRANTY

MODEL	COLOR TEMP	LED LENGTH	VOLTAGE	[2]PROFILE
SFS-35	**22K** 2200K **24K** 2400K **27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K **50K** 5000K	**100** 100 Ft. **[1]XX** per Ft. *1 = Custom length per FT. (cuttable every 1.97")	**24** 24V DC	[2]*See Page 3 - 5 for compatible profiles.* * Custom color finishes require powder coating. Allow 7 days leads time.

SAFIRE-35

UPDATED: 07.31.26

3.5W DESIGNER SERIES LED TAPE LIGHT

DIMENSIONS



LUMENS

MODEL	WATT	CCT	Lumen/ FT	EFFICACY (Lm/W)	CRI	R9	R13
SFS-35	3.5W	2200K	333	95	95+	85	98
		2400K	358	102	95+	91	99
		2700K	400	114	95+	94	98
		3000K	400	114	95+	95	99
		3500K	421	120	95+	94	98
		4000K	428	122	95+	92	98
		5000K	460	131	95+	96	99

COMPATIBLE CONNECTORS

*For more information about connector-profile compatibility, visit **corelightingusa.com/tape-light-accessories**.*

HP PRO CONNECTORS

QUICK CONNECT SNAP-ON
(0.95" X 0.57" X 0.30")

LSA-HW8-HPX10 8" HARDWIRE CONNECTOR
LSA-HW24-HPX10 24" HARDWIRE CONNECTOR
LSA-HW60-HPX10 60" HARDWIRE CONNECTOR
LSA-HW120-HPX10 120" HARDWIRE CONNECTOR


LSA-HW-HP

LSA-EX3-HPX10 3" LINK
LSA-EX8-HPX10 8" LINK
LSA-EX24-HPX10 24" LINK


LSA-EX-HP

LSA-DC24-HP-X10 24" DC CONNECTOR


LSA-DC-HP

MINI CRIMP CONNECTORS

QUICK CONNECT
(0.62" X 11.7" X 0.14")

LSA-HWPC-24-X10 24" HARDWIRE CONNECTOR

LSA-EXPC-3-X10 3" LINK



SAFIRE-35

UPDATED: 07.31.26

3.5W DESIGNER SERIES LED TAPE LIGHT

COMPATIBLE CONNECTORS

MALE/ FEMALE LINK CONNECTORS

HARDWIRE LINK CONNECTOR
100W (MAX POWER) | 4.5A (MAX RATING)
*SOLD SEPARATELY

CON6 6" HARDWIRE LINK CONNECTOR

CON24 24" HARDWIRE LINK CONNECTOR



COMPATIBLE ALUMINUM PROFILES

SURFACE PROFILES

ALU-SF
LENGTHS 39.4" | 78.9" | 84" | 98"
LENS Clear, Frosted
FINISH Black | Silver



ALU-CN (CORNER)
LENGTHS 39.4" | 78.9" | 84" | 98"
LENS Clear, Frosted
FINISH Black | Silver



ALP-20
LENGTHS 49.25" | 84" | 98.5"
LENS Frosted
FINISH White | Black | Silver



ALP-35
LENGTHS 48" | 96"
LENS Frosted
FINISH White | Black | Silver



ALP-50C-V2 (CORNER)
LENGTHS 48" | 84" | 98"
LENS Frosted
FINISH White | Black | Silver



ALP-50K-98
LENGTHS 39⅜" | 78⅞" | 98.5"
LENS Clear, Frosted
FINISH Black | Silver



ALP-60
LENGTHS 49.25" | 84" | 98.5"
LENS Frosted
FINISH White | Black | Silver



ALP-65
LENGTHS 48" | 96"
LENS Frosted
FINISH Silver



** For more compatible profiles, visit corelightingusa.com*

SAFIRE-35

3.5W DESIGNER SERIES LED TAPE LIGHT

UPDATED: 07.31.26

COMPATIBLE ALUMINUM PROFILES

SURFACE PROFILES

ALP-70

LENGTHS 49.25" | 84" | 98.5"
LENS Frosted
FINISH White | Black | Silver



ALP-80

LENGTHS 49.25" | 98.5"
LENS Frosted
FINISH Silver



ALP-100K-98 (CORNER)

LENGTHS 98.5"
LENS Frosted
FINISH Silver



** For more compatible profiles, visit corelightingusa.com*

RECESSED PROFILES

ALP-20R

LENGTHS 49.25" | 98.5"
LENS Frosted
FINISH White | Black | Silver



ALP-60R

LENGTHS 49.25" | 84" | 98.5"
LENS Frosted
FINISH White | Black | Silver



ALP-70R

LENGTHS 48" | 98"
LENS Frosted
FINISH Black | Silver



ALP-102R

LENGTHS 49" | 98"
LENS Frosted
FINISH Silver



** For more compatible profiles, visit corelightingusa.com*

SAFIRE-35

3.5W DESIGNER SERIES LED TAPE LIGHT

UPDATED: 07.31.26

COMPATIBLE ALUMINUM PROFILES

TRIMLESS PROFILES

ALP-1300TL

LENGTHS 48" | 98"
LENS Clear, Frosted
FINISH White



ALP-2100TL

LENGTHS 48" | 96"
LENS Clear, Frosted
FINISH White



ALP-2200TL

LENGTHS 48" | 96"
LENS Frosted
FINISH White



ALP-2300TL

LENGTHS 48" | 96"
LENS Frosted
FINISH White



ALP-2400TL

LENGTHS 48" | 96"
LENS Clear, Frosted
FINISH White



ALP-2500TL

LENGTHS 78"
LENS Clear, Frosted
FINISH White



ALP-2600TL

LENGTHS 78"
LENS Frosted
FINISH White



ALP-2700TL

LENGTHS 48" | 96"
LENS Frosted
FINISH White



** For more compatible profiles, visit corelightingusa.com*

SAFIRE-35

3.5W DESIGNER SERIES LED TAPE LIGHT

UPDATED: 07.31.26

COMPATIBLE TRANSFORMERS

PSDL SERIES
TRIAC DIMMABLE

PSDL-30W-24V	CLASS 2	6.5” X 3.63” X 1.03”
PSDL-60W-24V	CLASS 2	7.4” X 3.63” X 1.03”
PSDL-96W-24V	CLASS 2	8.67” X 3.67 X 1.62”
PSDL-150W-24V		8.67” X 3.67” X 1.62”
PSDL-192W-24V	CLASS 2	10.25” X 4.06” X 1.82”
PSDL-200W-24V		10.25” X 4.06” X 1.82”
PSDL-288W-24V	CLASS 2	10.25” X 4.06” X 1.82”
PSDL-300W-24V		10.25” X 4.06” X 1.82”



PSDH SERIES
HIGH PERMORMANCE MAGNETIC LOW VOLTAGE (MLV)

PSDH-48W-24V	CLASS 2	11.25” X 3.37” X 3.25”
PSDH-96W-24V	CLASS 2	11.25” X 3.37” X 3.25”



PSRX SERIES
4-IN-1 DIMMING DRIVER

PSRX-30W-24V	CLASS 2	6.5” X 3.72” X 1.57”
PSRX-60W-24V	CLASS 2	7.4” X 3.72” X 1.57”
PSRX-96W-24V	CLASS 2	8.66” X 3.72” X 1.57”
PSRX-150W-24V		10.24” X 4.13” X 1.77”
PSRX-192W-24V	CLASS 2	11" X 4" X 1.82"
PSRX-200W-24V		10.24” X 4.13” X 1.77”
PSRX-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSRX-300W-24V		10.94” X 4.33” X 1.77”



PSVT SERIES
0-10V DIMMING DRIVER

PSVT-60W-24V	CLASS 2	7.4” X 3.72” X 1.57”
PSVT-96W-24V	CLASS 2	8.66” X 3.72” X 1.57”
PSVT-200W-24V		10.24” X 4.13” X 1.77”
PSVT-288W-24V	CLASS 2	11.85” X 4.25” X 1.81”
PSVT-300W-24V		10.94” X 4.33” X 1.77”



SAFIRE-35

UPDATED: 07.31.26

3.5W DESIGNER SERIES LED TAPE LIGHT

COMPATIBLE TRANSFORMERS

PSDE SERIES
0-10V DIMMING W/ JUNCTION BOX

PSDE-60W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"
PSDE-96W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"



LUTRON 1%
3-WIRE DIMMING

L3DA4U1UKL-CV240	CLASS 2	4.89" X 4" X 2.62"



LUTRON 1%

PSDE-96W-24V-ECO	CLASS 2	10.5" X 3.0" X 2.0"

COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES
NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"