

LNHV60 DUAL BEND

120V DUAL BEND NEONFLEX

LNHV60 is a 120V, high performance, flexible LED fixture, designed as a neon replacement without the need for an external power supply. Suitable for indoor and outdoor applications, the LNHV60 easily bends around contours and tight curves without being damaged.

SPECIFICATIONS

POWER CONSUMPTION	4W/ Ft.
LUMEN OUTPUT	220 Lm/ Ft. (30K)
CRI	90+
COLOR TEMPERATURE	27K/ 30K/ 40K
DIMMING	ELV/ TRIAC
MAXIMUM RUN LENGTH	100Ft.
CUT INTERVALS	Every 3 in.
OPERATING VOLTAGE	120V
STORAGE TEMPERATURE	-40°F (-40°C) ~ 176°F (80°C)
OPERATING TEMPERATURE	-40°F (-40°C) ~ 104°F (40°C)
BEAM ANGLE	120°
BENDING DIAMETER	9.45"
IP RATING	IP65 Outdoor/ Wet Location
CERTIFICATIONS	ETL, RoHS
LUMEN MAINTENANCE	50,000 Hrs.



FEATURES

- Dual Bend
- 120° Light Source
- 120V AC
- ELV/ TRIAC Dimming
- UV Resistant
- ETL (US and Canada)

* This product is factory-cut only. Do not field modify.




MODEL	COLOR TEMP	VOLTAGE	LENGTH	POWER FEED	POWER FEED LENGTH
LNHV60-DB	27K 2700K	120V 120 Volts	Per Foot Per Foot	IP65EF End Feed	HW36 36 Inch Power Feed
	30K 3000K				HW120 120 Inch Power Feed
	40K 4000K				HWXX Custom Length Power Feed


LNHV60 DUAL BEND

120V DUAL BEND NEONFLEX

DIMENSIONS



LIGHT DISTRIBUTION




LNHV60 DUAL BEND


120V DUAL BEND NEONFLEX

ACCESSORIES


LNHV60-MB
MOUNTING BRACKET
25 X 17 X 18.5mm



LNHV60-AC96
96" ALUMINUM PROFILE



LNHV60-AFX
FLEXIBLE ALUMINUM PROFILE



IP65 POWER FEED

IP65EF
END FEED

