

LNE-15 DUAL BEND

2.5W IP67 FLEXIBLE LED NEON SERIES

Project _____

Location _____

Quote/ Ref # _____

The **LNE-15 Dual Bend** is a flexible LED fixture that offers both high performance and affordability. Specifically designed a neon replacement, this fixture can bend **horizontally and vertically** around contours or tight curves without risk of damage. Able to provide up to 16 feet of continuous line of light, it's an ideal choice for indoor or outdoor applications where a sleek, smooth surface is desired.



SPECIFICATIONS

POWER CONSUMPTION	Up to 2.5W per Ft.
LUMEN OUTPUT	Up to 210 Lumens per Ft.
CRI	90+
COLOR TEMPERATURE	27K/ 30K/ 35K/ 40K/ 50K
DIMMING/ CONTROL	MLV, ELV, 0-10 and TRIAC
MAXIMUM RUN LENGTH	16 Ft.
CUT INTERVALS	Every 3.94 in. (100mm)
OPERATING VOLTAGE	24V DC
STORAGE TEMPERATURE	-40°F (-40°C) to 176°F (80°C)
OPERATING TEMPERATURE	-4°F (-20°C) to 113°F (45°C)
BEAM ANGLE	120°
IP RATING	IP67
CERTIFICATIONS	UL Listed
LUMEN MAINTENANCE	50,000 Hrs.

FEATURES

- High color consistency and smooth illumination
- Multiple CCT options available
- Continuous run length up to 16 Ft.
- Bottom, Side and End Feed options
- UL Listed (US and Canada)

LUMENS

CCT	LM/W	LM/ FT.
2700K	72	180
3000K	73	183
4000K	84	210

* This product is factory-cut only. Do not field modify.



MODEL	COLOR TEMP	VOLTAGE	LENGTH	POWER FEED	FEED LENGTH
LNE15-DB	27K 2700K	24 24V DC	Please refer to page 4 for exact cutting lengths.	BF Bottom Feed	HW3 3 Ft. Power Feed
	30K 3000K			SFL Side Feed Left	HW10 10 Ft. Power Feed
	35K 3500K			SFR Side Feed Right	HW15 15 Ft. Power Feed
	40K 4000K			EF End Feed	HW30 30 Ft. Power Feed
	50K 5000K				HW50 50 Ft. Power Feed




LNE-15 DUAL BEND

2.5W IP67 FLEXIBLE LED NEON SERIES


CORE
ARCHITECTURAL
LIGHTING

UPDATED: 10.02.26

DIMENSIONS




LIGHT DISTRIBUTION



AVERAGE BEAM ANGLE (50%): 111.6°

— c0/180, 111.3 lc= 207.7
— c30/210, 111.4 lc= 206.6
— c60/240, 112.0 lc= 205.2
— c90/270, 111.9 lc= 205.0


LNE15-DB-27K



AVERAGE BEAM ANGLE (50%): 111.5°

— c0/180, 111.7 lc= 211.7
— c30/210, 112.0 lc= 211.3
— c60/240, 111.6 lc= 211.3
— c90/270, 110.6 lc= 212.1

LNE15-DB-30K



AVERAGE BEAM ANGLE (50%): 110.9°

— c0/180, 111.7 lc= 245.4
— c30/210, 112.0 lc= 245.4
— c60/240, 109.8 lc= 245.3
— c90/270, 110.0 lc= 245.5



LNE15-DB-40K

COMPATIBLE ACCESSORIES

SELF LOCKING ALUMINUM PROFILE



LNE15-AC2
2" PROFILE

LNE15-AC39
39" PROFILE



FLEXIBLE ALUMINUM PROFILE

LNE15-AFX39
39" PROFILE




LNE-15 DUAL BEND

2.5W IP67 FLEXIBLE LED NEON SERIES


CORE
ARCHITECTURAL
LIGHTING

UPDATED: 10.02.26


POWER FEEDS




BF
BOTTOM FEED




SFL
SIDE LEFT FEED



SFR
SIDE RIGHT FEED



EF
END FEED



LNE-15 DUAL BEND

2.5W IP67 FLEXIBLE LED NEON SERIES

CUTTING LENGTHS

LNE-15 Dual Bend is cuttable every **3.94" (10CM)**. Please refer to the chart below to determine actual lengths once LED is cut versus actual lengths required or specified.

Total Length Calculation = LNE Neon Series Length + End Feed option Length

Example: 59.7" Total Length = LNE Neon Series (59.1") + (0.60") End Feed

POWER FEED OPTION	LENGTH
END FEED	0.60 INCHES

* Minimum Run Length is 3.94"

CUTTING LENGTH INCREMENT TABLE

LENGTH (IN)	LENGTH (IN)	LENGTH (IN)
3.94	82.74	161.54
7.88	86.68	165.48
11.82	90.62	169.42
15.76	94.56	173.36
19.7	98.5	177.3
23.64	102.44	181.24
27.58	106.38	185.18
31.52	110.32	189.12
35.46	114.26	
39.4	118.2	
43.34	122.14	
47.28	126.08	
51.22	130.02	
55.16	133.96	
59.1	137.9	
63.04	141.84	
66.98	145.78	
70.92	149.72	
74.86	153.66	
78.8	157.6	


LNE-15 DUAL BEND

2.5W IP67 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS


PSDL SERIES TRIAC DIMMABLE

PSDL-30W-24V	CLASS 2	6.5" X 3.63" X 1.03"
PSDL-60W-24V	CLASS 2	7.4" X 3.63" X 1.03"
PSDL-96W-24V	CLASS 2	8.67" X 3.67 X 1.62"
PSDL-150W-24V		8.67" X 3.67" X 1.62"
PSDL-192W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-200W-24V		10.25" X 4.06" X 1.82"
PSDL-288W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-300W-24V		10.25" X 4.06" X 1.82"




PSDH SERIES HIGH PERFORMANCE MAGNETIC LOW VOLTAGE (MLV)

PSDH-48W-24V	CLASS 2	11.25" X 3.37" X 3.25"
PSDH-96W-24V	CLASS 2	11.25" X 3.37" X 3.25"




PSRX SERIES 4-IN-1 DIMMING DRIVER

PSRX-30W-24V	CLASS 2	6.5" X 3.72" X 1.57"
PSRX-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSRX-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSRX-150W-24V		10.24" X 4.13" X 1.77"
PSRX-192W-24V	CLASS 2	11" X 4" X 1.82"
PSRX-200W-24V		10.24" X 4.13" X 1.77"
PSRX-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSRX-300W-24V		10.94" X 4.33" X 1.77"



PSVT SERIES 0-10V DIMMING DRIVER

PSVT-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSVT-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSVT-200W-24V		10.24" X 4.13" X 1.77"
PSVT-288W-24V	CLASS 2	11.85" X 4.25" X 1.81"
PSVT-300W-24V		10.94" X 4.33" X 1.77"



LNE-15 DUAL BEND


2.5W IP67 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS

PSDE SERIES

0-10V DIMMING W/ JUNCTION BOX


PSDE-60W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"
PSDE-96W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"



LUTRON 1%

3-WIRE DIMMING

L3DA4U1UKL-CV240	CLASS 2	4.0" X 1.5" X 4.0"
------------------	---------	--------------------



PSDE-96W-24V-ECO	CLASS 2	10.5" X 3.0" X 2.0"
------------------	---------	---------------------



COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES

NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"

