


LNT-45

4.4W IP65 FLEXIBLE LED NEON SERIES

LNT45 is a high performance flexible LED fixture designed as a neon replacement. Suitable for indoor and outdoor applications, the LNT45 easily bends around contours and tight curves without being damaged. It allows for easy installation with its factory sealed terminators and self-locking male and female barrel connectors.

SPECIFICATIONS

INPUT VOLTAGE	24V DC Constant Voltage
POWER CONSUMPTION	3.66W per Ft.
LUMEN OUTPUT	143 Lm/ Ft.
CRI	88+
COLOR TEMPERATURE	27K/ 30K/ 40K/ BL
DIMMING/ CONTROL	MLV, ELV, 0-10 and TRIAC
MAXIMUM RUN LENGTH	32 Ft.
MINIMUM RUN LENGTH	6.56 in.
CUT INTERVALS	Every 83.3mm (3.28 in)
POWER FACTOR	≤ 1
STORAGE TEMPERATURE	-40°F (-40°C) to 140°F (60°C)
OPERATING TEMPERATURE	-40°F (-40°C) to 131°F (55°C)
BEAM ANGLE	160°
HUMIDITY	0-95% Non Condensing
IP RATING	IP65
CERTIFICATIONS	UL Listed
LUMEN MAINTENANCE	50,000 Hrs.



FEATURES

- High color consistency
- Smooth illumination
- Continuous run length up to 32 Ft.
- Dimmable with CORE dimmable drivers
- UL Listed (US and Canada)

* This product is factory-cut only. Do not field modify.





MODEL	LENS	COLOR TEMP	LENGTH	VOLT	INPUT	FEED LENGTH	OUTPUT	FEED LENGTH*
LNT-45	F Flat	27K 2700K	Please refer to page 5 for exact cutting lengths.	24 24V DC	EF End Feed	HW36 36 In. Power Feed	EF End Feed	HW36 36 In. Power Feed
		30K 3000K				HW120 120 In. Power Feed	EC End Cap	HW120 120 In. Power Feed
		40K 4000K						
		BL Blue						

* Not compatible with
End Cap (EC)


LNT-45

4.4W IP65 FLEXIBLE LED NEON SERIES

DIMENSIONS



HORIZONTAL BEND




* LED strip only bends along horizontal axis. Bending the LED strip vertically (perpendicular) to the light surface risks damage to the LED strip. Do **NOT** bend more than the indicated bend radius (shown above). Doing so will damage the LED strip.

COMPATIBLE ACCESSORIES

SELF LOCKING ALUMINUM PROFILE

LNT45-AC2
1.38" PROFILE


LNT45-AC39
39" PROFILE



LNT45-AC2




LNT45-AC39



FLEXIBLE ALUMINUM CHANNEL



LNT45-AFX
39" CHANNEL




FLEXIBLE PROFILE

LNT45-SPX39-WH
39" PROFILE (WHITE)

LNT45-SPX39-BK
39" PROFILE (BLACK)



LNT45-BKT-ADJ
ADJUSTABLE BRACKET




LNT-45



4.4W IP65 FLEXIBLE LED NEON SERIES

POWER FEED

IP65EF
END FEED



IP65EC
END CAP



LNT-45

4.4W IP65 FLEXIBLE LED NEON SERIES

CUTTING LENGTHS

LNT-45 Series is cuttable every **3.28" (8.33CM)**. Please refer to the chart below to determine actual lengths once LED is cut versus actual lengths required or specified.

Total Length Calculation = LNT Neon Series Length + End Feed option Length

Example: 50.73" Total Length = LNT Neon Series (49.2") + (1.53") End Feed

POWER FEED OPTION	LENGTH
END FEED	1.53 INCHES

* Minimum Run Length is 6.56".

CUTTING LENGTH INCREMENT TABLE


LENGTH (IN)	LENGTH (IN)	LENGTH (IN)
6.56	137.76	268.96
9.84	141.04	272.24
13.12	144.32	275.52
16.4	147.6	278.8
19.68	150.88	282.08
22.96	154.16	285.36
26.24	157.44	288.64
29.52	160.72	291.92
32.8	164	295.2
36.08	167.28	298.48
39.36	170.56	301.76
42.64	173.84	305.04
45.92	177.12	308.32
49.2	180.4	311.6
52.48	183.68	314.88
55.76	186.96	318.16
59.04	190.24	321.44
62.32	193.52	324.72
65.6	196.8	328
68.88	200.08	331.28
72.16	203.36	334.56
75.44	206.64	337.84
78.72	209.92	341.12
82	213.2	344.4
85.28	216.48	347.68
88.56	219.76	350.96
91.84	223.04	354.24
95.12	226.32	357.52
98.4	229.6	360.8
101.68	232.88	364.08
104.96	236.16	367.36
108.24	239.44	370.64
111.52	242.72	373.92
114.8	246	377.2
118.08	249.28	380.48
121.36	252.56	383.76
124.64	255.84	
127.92	259.12	
131.2	262.4	
134.48	265.68	

4.4W IP65 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS


PSDL SERIES TRIAC DIMMABLE

PSDL-30W-24V	CLASS 2	6.5" X 3.63" X 1.03"
PSDL-60W-24V	CLASS 2	7.4" X 3.63" X 1.03"
PSDL-96W-24V	CLASS 2	8.67" X 3.67 X 1.62"
PSDL-150W-24V		8.67" X 3.67" X 1.62"
PSDL-192W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-200W-24V		10.25" X 4.06" X 1.82"
PSDL-288W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-300W-24V		10.25" X 4.06" X 1.82"




PSDH SERIES HIGH PERFORMANCE MAGNETIC LOW VOLTAGE (MLV)

PSDH-48W-24V	CLASS 2	11.25" X 3.37" X 3.25"
PSDH-96W-24V	CLASS 2	11.25" X 3.37" X 3.25"




PSRX SERIES 4-IN-1 DIMMING DRIVER

PSRX-30W-24V	CLASS 2	6.5" X 3.72" X 1.57"
PSRX-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSRX-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSRX-150W-24V		10.24" X 4.13" X 1.77"
PSRX-192W-24V	CLASS 2	11" X 4" X 1.82"
PSRX-200W-24V		10.24" X 4.13" X 1.77"
PSRX-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSRX-300W-24V		10.94" X 4.33" X 1.77"



PSVT SERIES 0-10V DIMMING DRIVER

PSVT-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSVT-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSVT-200W-24V		10.24" X 4.13" X 1.77"
PSVT-288W-24V	CLASS 2	11.85" X 4.25" X 1.81"
PSVT-300W-24V		10.94" X 4.33" X 1.77"



LNT-45


4.4W IP65 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS

PSDE SERIES

0-10V DIMMING W/ JUNCTION BOX


PSDE-60W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"
PSDE-96W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"




LUTRON 1%

3-WIRE DIMMING

L3DA4U1UKL-CV240	CLASS 2	4.89" X 4" X 2.62"
------------------	---------	--------------------



PSDE-96W-24V-ECO	CLASS 2	10.5" X 3.0" X 2.0"
------------------	---------	---------------------



COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES

NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"

