


LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

LNT45 is a high performance flexible LED fixture designed as a neon replacement. Suitable for indoor and outdoor applications, the LNT45 easily bends around contours and tight curves without being damaged. It allows for easy installation with its factory sealed terminators and self-locking male and female barrel connectors.

SPECIFICATIONS

INPUT VOLTAGE	24V DC Constant Voltage
POWER CONSUMPTION	3.66W per Ft.
LUMEN OUTPUT	143 Lm/ Ft.
CRI	88+
COLOR TEMPERATURE	22K / 27K / 30K / 35K / 40K / 50K RD / GN / BL / AM / PK / YW
DIMMING/ CONTROL	MLV, ELV, 0-10 and TRIAC
MAXIMUM RUN LENGTH	32 Ft.
MINIMUM RUN LENGTH	6.56 in.
CUT INTERVALS	Every 83.3mm (3.28 in)
POWER FACTOR	≤1
STORAGE TEMPERATURE	-40°F (-40°C) to 140°F (60°C)
OPERATING TEMPERATURE	-40°F (-40°C) to 131°F (55°C)
BEAM ANGLE	160° (Flat) 270° (Dome)
HUMIDITY	0-95% Non Condensing
IP RATING	IP67/ 68
CERTIFICATIONS	UL Listed
LUMEN MAINTENANCE	50,000 Hrs.



FEATURES

- High color consistency
- Smooth illumination
- Continuous run length up to 32 Ft.
- Waterproof, submersible under water
- Bottom, Side and End Feed options
- UL Listed (US and Canada)

*This product is factory-cut only. Do not field modify.




MODEL	LENS	COLOR TEMP		LENGTH	VOLT	INPUT	FEED LENGTH	OUTPUT	FEED LENGTH*
LNT-45	F Flat	22K 2200K	RD Red	Please refer to page 5 for exact cutting lengths.	24 24V DC	BF Bottom Feed	HW3 3 Ft. Power Feed	BF Bottom Feed	HW3 3 Ft. Power Feed
	D Dome	27K 2700K	GN Green			SFL Side Feed Left	HW10 10 Ft. Power Feed	SFL Side Feed Left	HW10 10 Ft. Power Feed
		30K 3000K	BL Blue				HW16 16 Ft. Power Feed		HW16 16 Ft. Power Feed
		35K 3500K	AM Amber			SFR Side Feed Right	HW32 32 Ft. Power Feed	SFR Side Feed Right	HW32 32 Ft. Power Feed
		40K 4000K	PK Pink				HW50 50 Ft. Power Feed		HW50 50 Ft. Power Feed
		50K 5000K	YW Yellow						
		60K 6000K							
*Not compatible with End Cap (EC)									

LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

DIMENSIONS




COMPATIBLE ACCESSORIES

SELF LOCKING ALUMINUM PROFILE

LNT45-AC2
1.38" PROFILE


LNT45-AC39
39" PROFILE



LNT45-AC2




LNT45-AC39





PLASTIC PROFILE

LNT45-PC39
39" PROFILE



FLEXIBLE ALUMINUM CHANNEL

LNT45-AFX
39" CHANNEL



LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

COMPATIBLE ACCESSORIES


FLEXIBLE PROFILE

LNT45-SPX39-WH
39" PROFILE (WHITE)

LNT45-SPX39-BK
39" PROFILE (BLACK)



LNT45-BKT-ADJ
ADJUSTABLE BRACKET



RACEWAY PROFILE

LNT45-SMR-AC39-SI
39" PROFILE (SILVER)

LNT45-SMR-AC39-WH
39" PROFILE (WHITE)

*Made to Order.

LNT45-SMR-AC39-BK
39" PROFILE (BLACK)

*Made to Order.


LNT45-SMR-EC
END CAPS

* Set of 2 (1 with Hole and 1 without Hole)


* Sold Separately

LNT45-SMR-SC
JOINER BRACKET


* Sold Separately



LNT45-SMR-AC39



LNT45-SMR-EC




LNT45-SMR-JB

LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

IP67/68 POWER FEED



LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

CUTTING LENGTHS

LNT-45 Series is cuttable every **3.28" (8.33CM)**. Please refer to the chart below to determine actual lengths once LED is cut versus actual lengths required or specified.

Total Length Calculation = LNT Neon Series Length + End Feed option Length

Example: 50.3" Total Length = LNT Neon Series (49.2") + (1.1") End Feed

* Minimum Run Length is 6.56".

POWER FEED OPTION	
END FEED	1.1"
BOTTOM FEED	0.20"
SIDE FEED	0.20"

CUTTING LENGTH INCREMENT TABLE

LENGTH (IN)	LENGTH (IN)	LENGTH (IN)
6.56	137.76	268.96
9.84	141.04	272.24
13.12	144.32	275.52
16.4	147.6	278.8
19.68	150.88	282.08
22.96	154.16	285.36
26.24	157.44	288.64
29.52	160.72	291.92
32.8	164	295.2
36.08	167.28	298.48
39.36	170.56	301.76
42.64	173.84	305.04
45.92	177.12	308.32
49.2	180.4	311.6
52.48	183.68	314.88
55.76	186.96	318.16
59.04	190.24	321.44
62.32	193.52	324.72
65.6	196.8	328
68.88	200.08	331.28
72.16	203.36	334.56
75.44	206.64	337.84
78.72	209.92	341.12
82	213.2	344.4
85.28	216.48	347.68
88.56	219.76	350.96
91.84	223.04	354.24
95.12	226.32	357.52
98.4	229.6	360.8
101.68	232.88	364.08
104.96	236.16	367.36
108.24	239.44	370.64
111.52	242.72	373.92
114.8	246	377.2
118.08	249.28	380.48
121.36	252.56	383.76
124.64	255.84	
127.92	259.12	
131.2	262.4	
134.48	265.68	


LNT-45

4.4W IP67/68 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS


PSDL SERIES TRIAC DIMMABLE

PSDL-30W-24V	CLASS 2	6.5" X 3.63" X 1.03"
PSDL-60W-24V	CLASS 2	7.4" X 3.63" X 1.03"
PSDL-96W-24V	CLASS 2	8.67" X 3.67 X 1.62"
PSDL-150W-24V		8.67" X 3.67" X 1.62"
PSDL-192W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-200W-24V		10.25" X 4.06" X 1.82"
PSDL-288W-24V	CLASS 2	10.25" X 4.06" X 1.82"
PSDL-300W-24V		10.25" X 4.06" X 1.82"




PSDH SERIES HIGH PERFORMANCE MAGNETIC LOW VOLTAGE (MLV)

PSDH-48W-24V	CLASS 2	11.25" X 3.37" X 3.25"
PSDH-96W-24V	CLASS 2	11.25" X 3.37" X 3.25"




PSRX SERIES 4-IN-1 DIMMING DRIVER

PSRX-30W-24V	CLASS 2	6.5" X 3.72" X 1.57"
PSRX-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSRX-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSRX-150W-24V		10.24" X 4.13" X 1.77"
PSRX-192W-24V	CLASS 2	11" X 4" X 1.82"
PSRX-200W-24V		10.24" X 4.13" X 1.77"
PSRX-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSRX-300W-24V		10.94" X 4.33" X 1.77"



PSVT SERIES 0-10V DIMMING DRIVER

PSVT-60W-24V	CLASS 2	7.4" X 3.72" X 1.57"
PSVT-96W-24V	CLASS 2	8.66" X 3.72" X 1.57"
PSVT-200W-24V		10.24" X 4.13" X 1.77"
PSVT-288W-24V	CLASS 2	11.85" X 4.25" X 1.81"
PSVT-300W-24V		10.94" X 4.33" X 1.77"




4.4W IP67/68 FLEXIBLE LED NEON SERIES

COMPATIBLE TRANSFORMERS

PSDE SERIES

0-10V DIMMING W/ JUNCTION BOX


PSDE-60W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"
PSDE-96W-24V-010-JB	CLASS 2	12.1" X 2.36" X 1.4"




LUTRON 1%

3-WIRE DIMMING

L3DA4U1UKL-CV240	CLASS 2	4.89" X 4" X 2.62"
------------------	---------	--------------------



PSDE-96W-24V-ECO	CLASS 2	10.5" X 3.0" X 2.0"
------------------	---------	---------------------



COMPATIBLE NON-DIMMING DRIVERS

PSHK SERIES

NON-DIMMING CONSTANT VOLTAGE WITH JUNCTION BOX

PSHK-30W-24V	CLASS 2	6.5" X 3.6" X 1.02"
PSHK-60W-24V	CLASS 2	7.4" X 3.62" X 1.02"
PSHK-96W-24V	CLASS 2	8.66" X 3.66" X 1.61"
PSHK-150W-24V		10.24" X 4.06" X 1.81"
PSHK-200W-24V		10.24" X 4.06" X 1.81"
PSHK-288W-24V	CLASS 2	11.85" X 4.25" X 1.82"
PSHK-300W-24V		10.24" X 4.25" X 1.81"

